

### Coverage Rate

1. The coverage rate varies from 160 square feet per gallon for extremely porous brick and stone to 225 square feet per gallon for more dense brick and stone. Very tight-grained stone and polished brick can be as high as 280 square feet per gallon.
2. Only one coat application is required.
3. Existing conditions should be reviewed before the application. A recommended starting application is 225 square feet per gallon. ***A test section may help determine the correct application rate.***

### Application on Wall/Vertical Brick and Stone

1. Thoroughly clean the surface to be treated with water. Ensure any existing surface treatments, mold, mildew, and algae have been removed before rinsing and washing with water.
2. Allow the surface to dry before application. Brick and Stone Cover must be applied to a dry surface.
3. **Shake well before use.** Do not dilute or mix with other liquids.
4. Application is typically done with a low-pressure sprayer but can also be done with a brush or roller.
5. Will not fill or seal visible existing cracks. Existing cracks should be treated before application.
6. Avoid application during direct exposure to sun or wind: too rapid evaporation could lead to slight imperfections of the treated surface. An example would be a sun-facing wall during a hot sunny day.
7. Only apply when the surface temperature is 50 degrees F and will not drop below 40 degrees F for the next 8 hours, and below 90 degrees F for the next 8 hours.
8. The reaction time is 3-5 hours. The application will withstand light rain after 12 hours and heavy rain after 24 hours.
9. Typical applications last an average of 10 years or longer before needing reapplication. The reapplication rate will be less than the original application rate, so always treat a test section first to determine the reapplication rate.
10. The typical application lasts 5 to 7 years for an average private swimming pool environment. The reapplication rate will be less than the typical application rate.

### Application on Flat/Horizontal Brick and Stone

1. Thoroughly clean the surface to be treated with water. Ensure any existing surface treatments, mold, mildew, and algae have been removed before rinsing and washing with water.
2. Allow the surface to dry before application. Brick and Stone Cover must be applied to a dry surface.
3. **Shake well before use.** Do not dilute or mix with other liquids.
4. Application is typically done with a low-pressure sprayer but can also be done with a brush or roller.
5. Will not fill or seal visible existing cracks. Existing cracks should be treated before application.
6. Avoid application during direct exposure to sun or wind: too rapid evaporation could lead to slight imperfections of the treated surface. An example would be a sun-facing wall during a hot sunny day.
7. Only apply when the surface temperature is 50 degrees F and will not drop below 40 degrees F for the next 8 hours, and below 90 degrees F for the next 8 hours.
8. The reaction time is 3-5 hours. The application will withstand light rain after 12 hours and heavy rain after 24 hours.
9. Typical applications last an average of 10 years or longer before needing reapplication. The reapplication rate will be less than the original application rate, so always treat a test section first to determine the reapplication rate.
10. The typical application lasts 5 to 7 years for an average private swimming pool environment. The reapplication rate will be less than the typical application rate.

### Storage Requirements and Warnings

1. Protect the product from freezing during storage. Contact the manufacturer if the product has been frozen. Maintain and ensure all seals are tight to prevent evaporation and contamination. Protect storage containers from ultraviolet and environmental damage.
2. Protect non-absorbent surfaces, glass, and aluminum during application. Be cautious of overspray during windy conditions.
3. Always wear personal protection equipment required for work.
4. Keep out of reach of children.